


**NOTES:**  
 1. FOR SPECIFICATION AND PERFORMANCE CHARACTERISTICS SEE CA DWG 100252  
 2. **ENVIRONMENTAL:**  
 TEMPERATURE RANGE -20°C TO +85 °C  
 3. **ELECTRICAL:**  
 RATED: 1.5A @ 40V AC (rms)  
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.  
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.  
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC (rms)  
 4. **MECHANICAL:**  
 MATING FORCE: 10 LB. [4.5 kg] MAX.  
 UNMATING FORCE: 2.2 LB. [1 kg] MIN, 8.8 LB. [4 kg] MAX.  
 5. **MATERIAL:**  
 HOUSING: GLASS FILLED THERMOPLASTIC, NATURAL, UL 94V-0  
 CONTACT: PHOSPHOR BRONZE  
 SHELL: ZINC ALLOY, NICKEL PLATED  
 BOARD LOCK: COPPER ALLOY, TIN PLATE  
 6. **PART NO.**

907 A X 29 F X A X 0 5  
 1 2 3 4 5 6 7 8 9 10

- 1. **SERIES NO.**
- 2. **TYPE:**  
 A=Standard
- 3. **ENVIRONMENT PROTECTION MATERIAL.**  
 -=General  
 E=RoHS
- 4. **CONTACT NUMBER**  
 29=(INTEGRATED: DIGITAL /ANALOG)
- 5. **CONTACT TYPE:**  
 F=FEMALE
- 6. **CONTACT PLATING:**  
 S=Gold Flash (Selective)  
 C=15u" Gold (Selective)  
 D=30u" Gold (Selective)
- 7. **MOUNTING TYPE:**  
 A=ATX FORK R/A  
 PCB LAYOUT
- 8. **PARTS OPTION**  
 0=NON ACCESSORIES  
 1=4-40 UNC HEX SCREWLOCK
- 9. **INSERTING OPTION**  
 0=DVI CONNECTORS
- 10. **INSULATOR COLOR**  
 5=BEIGE



RECOMMENDED P.C.B. LAYOUT TOLERANCES: ±0.05mm

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2
SCALE: AS SHOWN	UNIT: mm

**MC-COMPONENTS**

C	ECN-0702067(Sally) (10,A)	02/08/07	DRAWN	JOE	02/12/07	DRAWN NAME:	DVI CONNECTORS	
B	ECN-0612037(Sally) (7,D)	12/04/06	CHECKED	pearl	02/14/07		INTEGRA TED 29-RIGHT ANGLE	
A		10/09/00	APPROVED	Blank	02/14/07	PRODUCT NO.	907AX29FXAX05	
REV.	DESCRIPTION	DATE	SIZE	A4	REV.	C	FILE NAME:	907AE29FXAX05(37)